

SunWeld Order Checklist - Entire System



SPECIFICATIONS

1: GLAZING MATERIAL

	INNER	OUTER
ACRYLIC DOME	<input type="checkbox"/>	<input type="checkbox"/>
POLYCARBONATE DOME	<input type="checkbox"/>	<input type="checkbox"/>

2: GLAZING COLOR

CLEAR	<input type="checkbox"/>	<input type="checkbox"/>
BRONZE	<input type="checkbox"/>	<input type="checkbox"/>
WHITE	<input type="checkbox"/>	<input type="checkbox"/>
OTHER _____	<input type="checkbox"/>	<input type="checkbox"/>

3: FRAME FINISH

MILL	<input type="checkbox"/>
BRONZE PAINT	<input type="checkbox"/>
CLEAR ANODIZED	<input type="checkbox"/>
CUSTOM COLOR _____	<input type="checkbox"/>

4: INSULATED SELF CURB

COMMERCIAL 9" -STANDARD	<input type="checkbox"/>
COMMERCIAL 12"	<input type="checkbox"/>
CUSTOM _____	<input type="checkbox"/>

5: PYRAMID PITCH (OPTIONAL)

STANDARD 26 DEGREE (6/12)	<input type="checkbox"/>
CUSTOM _____ DEGREE ()	<input type="checkbox"/>

6: OTHER OPTIONS

THERMALLY BROKEN SASH (TB)

FOR SELF FLASHING SKYLIGHTS (DECK MOUNT)
PROVIDE ROUGH OPENING DIMENSION

QTY: _____ R.O. = _____ X _____

DATE: _____ ORDER #: _____

PROJECT: _____ LOCATION: _____

CUSTOMER: _____ APPROVED: _____

- ① 1" Rigid Insulation
- ②a Alum. Extruded Sash Non TB w/ weep holes
- ②b Alum. Extruded Sash TB w/o weep holes
- ③ S.S. Fastener
- ④ Alum. Extruded Retaining angle
- ⑤ Glazing tape spacer

- ⑥ Sealant tape
- ⑦ Outer Dome
- ⑧ Inner Dome
- ⑨ Condensation Gutter
- ⑩ Weather stripping tape
- ⑪ Glazing Tape (Typ.)
- ⑫ Aluminum skin

