

**CAV-GRIP 3V for use with EPDM**  
**December 7, 2018**

**To: Versico Roofing Systems' Authorized Contractors**

Versico Roofing Systems is excited to announce that CAV-GRIP 3V Low-VOC Adhesive/Primer can now be used to bond VersiGard® EPDM to horizontal substrates for warranty terms up to and including 20-year, 90-mph designs. CAV-GRIP 3V provides substantial productivity-boosting advantages on the jobsite:

- Can be used in temperatures as low as 25°F (-4°C)
- VOC compliant and very low odor
- Quick application with spray gun
- Fast tack time (< 5 minutes)
- No stirring and easy clean-up
- Up to 60% labor savings compared to traditional bonding adhesive applications

CAV-GRIP 3V packaging options and supporting accessories are listed below.

Description	Product Code	Packaging	Weight	Stocking Location(s)	Coverage Rate*
CAV-GRIP 3V - #40 Cylinder	330420	#40 Cylinder	40 lb	C, G, S, T	1,000 ft <sup>2*</sup>
CAV-GRIP 3V - #85 Cylinder	332800	12 per pallet	85 lb	Direct Ship	2,000 ft <sup>2*</sup>
Low-VOC UN-TACK	330793	#8 Cylinder	14 lb	C, T	N/A
Spray Gun w/24" Extension**	330912	Each	2 lb	C, T	N/A
CAV-GRIP 6' Hose	304302	Each	1 lb	C, G, T, S	N/A
CAV-GRIP 12' Hose	304303	Each	2 lb	C, G, T, S	N/A
CAV-GRIP 18' Hose	304304	Each	3 lb	C, G, T	N/A
*Approximate double-sided adhesive application				**Hoses sold separately	

CAV-GRIP 3V has proven to be popular in previously approved applications, including adhering VersiGard EPDM membranes to vertical surfaces, adhering VersiWeld® TPO membranes, and as a primer for VapAir Seal™ 725TR. Contractors who used CAV-GRIP 3V in the test market have raved about the speed and ease of application, as well as the dramatic reduction in flash-off time. Please give CAV-GRIP 3V a try on your next adhered project.

If you have any questions, or for more information, please contact your independent sales representative.

Sincerely,



Ronald L. Goodman, EPDM Marketing Manager